

terms and conditions of the sale jointly with the original purchaser. The purchaser shall furnish a list of men allowed to enter the Forest and shall hold himself responsible for breach of any of the Forest Rules and for the occurrence of fire in the Plantation or Forest due either to himself or his men, which will be dealt with under the provision of the Mysore Forest Act.

6. The grazing will be permitted only between sunrise and sunset up to end of the period stipulated viz. 30th June 1939. No scraping or digging of grass is permitted.

7. The purchaser shall not interfere with any forest operation, such as planting, sowing and felling, that the Forest Department may wish to conduct in the leased area, should any damage be caused by such operations to the grass crop, he shall not be entitled to any compensation. He shall not graze in the area under cultural operations.

8. The lessee will be permitted to graze his cattle in the leased area only after the payment of the sale amount in full on such days as may be prescribed by the District Forest Officer.

9. Cattle that may be found grazing in the leased area before payment of the lease amount will be liable to be impounded.

10. In the event of a breach of any of the conditions specified in the sale notification, the lease is liable to be cancelled and a penalty not exceeding Rs. 25 levied and recovered as an arrear of land revenue by the District Forest Officer for every offence.

L. SRINIVASA MURTHY  
District Forest Officer.

## ENGINEERING DEPARTMENT

### BUILDINGS DIVISION, BANGALORE.

*Abstract Notification dated 3rd August 1939.*

The attention of the public is hereby invited to the detailed notification, calling for tenders for construction of First Floor for the Mathematics Block, Central College, Bangalore, published in pages 1535 and 1539, Part VI of the *Mysore Gazette*, dated 10th August 1939. The last date of tender is 26th August 1939.

M. K. RAJAN NINGAR  
Executive Engineer.

### BANGALORE DIVISION.

*Notification dated 15th August 1939.*

1. Sealed tenders will be received at the Office of the Executive Engineer, Bangalore Division, up to 2 P.M. on 4th September 1939, for the construction of a compound wall to the Electric Colony at Doddballapur.

2. Tenders in the prescribed form obtainable on payment of Rs. 0-4-0 per form from the Office of the Executive Engineer, Bangalore Division, should be addressed to the Executive Engineer, Bangalore Division, in a sealed cover and superscribed as "Tender for the construction of a compound wall to the Electric Colony at Doddballapur." The name of the tenderer should also be superscribed on the top of the cover.

3. Each tender must be accompanied by a duplicate cheque for having credited into the Treasury an amount of Rs. 100 under "17 (a) Public Works Deposits" Mysore Government Bonds, duly signed by the tenderer, face value or market value, whichever is less, as earnest money. The earnest money of the successful tenderer will be retained as security deposit for due fulfilment of the contract. Such deposit will not carry any interest.

4. The tenders will be opened in the presence of such tenderers who wish to be present on 5th September 1939 at 3 P.M. The final acceptance of the tender will rest with the Executive Engineer, who does not bind himself to accept the lowest or any tender, or to assign any reason whatever for the rejection of any.

5. The name of the successful tenderer will be posted on the Notice Board in the Executive Engineer's Office in due course. Within eight days of the acceptance of the tender, the successful tenderer will be required to execute an agreement in the departmental Schedule Contract Form for the due fulfilment of the contract, and for the execution of all items of work in accordance with the Bombay specifications (1931).

6. Failure to comply with the condition 5 above or to agree to carry out the work in accordance with the specifications and agreements in force will entail forfeiture of the earnest money.

7. The earnest money of rejected tenders will be returned on submission of the receipt originally granted, along with an application to the Executive Engineer.

8. Copies of contract documents, schedules and drawings may be seen at any time at the Executive Engineer's Office, Bangalore Division, Bangalore, on all working days, between 11 A.M. and 5 P.M. and may be obtained from that officer on payment of Rs. 3 for each.

9. Specific rates should be given for each item in the schedule accompanying the tender and the rates should be in rupees, annas and pies and expressed in words and figures. Tenders offering a percentage reduction on the estimate amount will be rejected.

10. Any rates or lumpsum amounts for the items not called for, if tendered by the tenderer, will not be taken notice of. The rates for such items may be entered in a separate schedule with date and reasons for the same.

11. No alterations which are made by the tenderers in the tender form in the nomenclature of the items of work will be recognised and if corrections are made, the tenders are liable to rejection.

12. There should be no alterations or erasures in the tenders in the rates of items and any corrections made in the rates should be attested to, and the number of corrections, if any, in each page, noted at the foot of the same by the tenderer.

13. No reference should be made to the Public Works Department schedule of rates.

14. In the event of the tender being submitted by a firm, it must be signed separately and severally by each member thereof, or in the event of absence of any partner, it must be signed on his behalf by a person holding power-of-attorney authorising him to do so.

15. When once the rates tendered have been accepted, they will not be revised under any circumstances. In regard to items of work not tendered, the rates for the same will be calculated by the Executive Engineer on the basis of current rates for materials and labour with a contractor's profit of 5 per cent as may be approved by the Superintending Engineer. This shall be final and legally binding on the tenderer.

16. The quantities given in the schedule are only approximate and the drawings shown to the contractor are only tentative and are liable to alterations, omissions, deductions, or additions at the discretion of the Executive Engineer or his representative. The tendered rates will hold good for any quantity, whether higher or lower than those given in the enclosed schedule.

17. The works should be completed and handed over in a tidy condition to the Public Works Department by the end of December 1939, failing which the Executive Engineer may, at his discretion, levy a penalty of Re. 1 per day which will ordinarily be calculated at 12 per cent per annum on the total outlay as liquidated damages for non-fulfilment of contract, and will be recovered from the contractor's outstandings for the period exceeded by him beyond the time fixed and until the work is completed and handed over.

18. In all matters of disputes of any kind not specially provided for in the agreement or of rates, penalties, measurements, quality of work, etc., the decision of the Chief or the Superintending Engineer, shall be final and legally binding.

19. No claim for damages for delays caused by officers of the department in the execution of the work will be considered, whatever may be the reasons for such delays. Contractors should bear this in mind when tendering for the work. Extension of time due to delays caused by the departmental officers will, however, be considered on the merits of each case.

20. The contract should not be sublet.

21. All materials, tools and plant and machinery that will be supplied by the Executive Engineer in the interest of the work shall be accepted by the tenderer at the rates fixed by the Executive Engineer. The tenderer will pay the hire on tools and plant and machinery as per rules from the date of taking over of such machinery, tools and plant from the Stores to the date of return thereto, the dates considered being the dates of acknowledgments of the vouchers in each transaction.

22. The contractor should arrange for the payment of royalty and tolls.

Note.—(a) The contractor should at his own cost—

- (1) Provide rods, stakes, ropes and labour required in setting out the works.
- (2) Provide all necessary scaffolding, centering, labour and appliances for hoisting.
- (3) Provide mortar mills and sheds, to keep materials under cover and also for workmen.
- (4) Arrange for protecting work during inclement weather.
- (5) Supply requisite temporary lights, water cisterns, water pumps and hoses, sieves, parahs, shoring, strutting and other requisite protective appliances during the progress of the work.
- (6) Supply all water required for work and workmen and shall provide temporary latrines and drains.
- (7) Clean away all dirt, rubbish, superfluous materials and debris as they accumulate.
- (8) Provide arrangements for pumping and baling of water from excavations and foundations wherever and whenever necessary with his own pumping apparatus including necessary leading drains, slump pits, etc.
- (9) Afford facilities to any other parties employed upon the work by the P. W. D., so that their work may proceed during the progress of the contract, and give such persons the use of ordinary scaffolding and ladders.
- (10) The contractor is responsible for all accidents to workmen, etc., on the work and he must take precaution against all risk of accidents and if necessary provide for the same by Insurance at the proper time.

(b) It is the business of the contractor to make his own arrangements for quarries and supplies of materials.

Approximate quantities for constructing the Compound Wall in front of *Police Colony* at Dodballapur.

| No. | Items of work                                                                                                                                                                                                  | Unit  | Rate      | Quantity | Rate to be quoted |            |
|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-----------|----------|-------------------|------------|
|     |                                                                                                                                                                                                                |       |           |          | In words          | In figures |
|     |                                                                                                                                                                                                                |       | Rs. a. p. |          | Rs. a. p.         | Rs. a. p.  |
| 1   | Constructing perforated burnt stone compound wall including earth-work, 4" coping slab with chamfered edges, burnt stone jelly concrete for foundations, cement pointing, etc., complete as per design .. .. . | R.ft. | 2 10 0    | 120      |                   |            |
| 2   | Refixing the existing gates after the pillars are built .. .. .                                                                                                                                                | Each  | ..        | 2        |                   |            |
| 3   | Constructing dressed pillars as per design .. .. .                                                                                                                                                             | "     | 75 0 0    | 4        |                   |            |

N. LAKSHMINARASIMHAIAH,  
*Executive Engineer*

#### BUREAU OF SANITARY ENGINEERING, BANGALORE

*Abstract Notification dated 17th August 1939.*

The attention of the public is invited to the notification calling for tenders for the work of "Improving distribution system of water supply for giving facilities for public house connections at Arsikere" published in page 1797, Part VI of the *Mysore Gazette*, dated 17th August 1939.

The last date of receiving tenders is fixed on 28th August 1939.

A. KRISHNANENGAR,  
*Sanitary Engineer*

#### KOLAR DIVISION

*Abstract Notification dated 20th August 1939.*

The attention of the public is invited to the detailed notification, dated 17th August 1939, published on pages 1596-1597, Part VI of the *Mysore Gazette*, dated 17th August 1939, for tenders for constructing a *Warehousing Building* at Kyalnoor, Kolar Taluk.

The last date for receiving tenders is 4th September 1939, up to 2 P.M.

C. R. LINGAR,  
*Executive Engineer*

#### TUMKUR DIVISION

*Notification dated 17th August 1939.*

Notice is hereby given that sealed tenders will be received at the Office of the Executive Engineer, Tumkur Division, up to 2 P.M., on 20th September 1939, for constructing two Blocks of Linemen's Quarters at Tiptur. An approximate estimate of quantities is given below. These quantities are not guaranteed. The work should be completed by the end of December 1939.

2. The plans, detailed estimate and conditions may be seen at the Executive Engineer's Office at Tumkur, between the hours of 11 A.M. and 5 P.M.

3. Tender should be submitted on printed forms which may be obtained by paying four annas from the Executive Engineer. The tenders should be accompanied by a statement in the form given below, showing the rates at which the different items specified will be executed.

4. Each tender must be accompanied by treasury challan of Rs. 264 credited to "17 (a) P. W. Deposits" as earnest money and be superscribed "Tender for constructing two Blocks of Linemen's Quarters at Tiptur", in default of which, tenders will be rejected.

5. The final acceptance of any tender will rest with the Executive Engineer, who does not bind himself to accept the lowest or any tender or to assign any reason whatever for the rejection of any tender.

6. Within eight days of the acceptance of the tender, the successful competitor will be required to execute the usual contract bond; in default of which his tender will be considered cancelled and his earnest money will be forfeited.

7. The name of the successful competitor, whose tender has been accepted, will be posted on the Notice Board in the Executive Engineer's Office in due course. No enquiry regarding the acceptance or rejection of a tender will receive any reply.

8. On acceptance of one of the tenders, the earnest money on rejected tenders will be returned.

9. Rates once tendered will not be enhanced on any account.

10. Rates for non-tendered and non-estimated items shall be as per schedule rates of the Department or those fixed by the Executive Engineer after working out data with not more than 10 per cent for contractor's profit.

11. In all matters not specifically provided for and in all matters of dispute about rates, quantities, measurements, quality of works, etc., and in all disputes of any kind, the decision of the Executive Engineer will be final and legally binding.

12. Quotations must be given in words as well as in figures and they must be in specific term of unit shown against each item of work. Any quotation quoted at so much percentage less or more than estimated rate will not be accepted.

Abstract estimate for two Blocks of eight Linemen's Quarters four in each, for Electrical Department at Tiptur Town.

| No.  | Description of work                                                                                                                                                                                   | Per   | Rate      | Quantity |
|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-----------|----------|
|      |                                                                                                                                                                                                       |       | Rs. a. p. |          |
| 1    | Earthwork excavation in gravelly soil and filling in basement including watering and tamping in layers 6" thick ..                                                                                    | C.yd. | 0 3 6     | 29       |
| 2    | Stone jelly (one inch size) concrete in lime mortar 1:2:4 for foundation laid in 4" layers and well tamped. ..                                                                                        | C.ft. | 0 3 6     | 309      |
| 3    | Stone in lime mortar in courses not less than 8" high with bond stones 6' apart in every course for foundations and for basement including all quoins dressed 2" wide at corners ..                   | "     | 0 4 3     | 741      |
| 4    | Burnt brick in clay superstructure ..                                                                                                                                                                 | "     | 0 3 0     | 1,475    |
| 4(a) | Burnt brick in lime mortar ..                                                                                                                                                                         | "     | 0 4 6     | 700      |
| 5    | Stone slabs 6" thick set in lime mortar with two line dressing for steps and all other exposed faces ..                                                                                               | S.ft. | 0 5 0     | 158      |
| 6    | Chunam plastering two coats including rounding off corners and smooth rendering ..                                                                                                                    | Sqr.  | 3 0 0     | 48'00    |
| 7    | Cement pointing with thread lines after scraping the joints to $\frac{1}{2}$ " to 1" deep ..                                                                                                          | "     | 3 8 0     | 1'50     |
| 8    | White and colour washing 2 coats ..                                                                                                                                                                   | "     | 0 4 6     | 48'00    |
| 9    | Roofing with first class Mangalore tiles on teakwood reepers nailed including wood oiling to reepers eave tiles being tiled by a teak batter ..                                                       | "     | 25 0 0    | 18'84    |
| 10   | Mangalore ridge tiles set in mortar and cement pointed complete ..                                                                                                                                    | R.ft. | 0 8 0     | 64       |
| 11   | Ventilating tiles fixed complete double ..                                                                                                                                                            | Each  | 4 0 0     | 16       |
| 12   | Teakwood wrought and put up with wood oiling 2 coats with provision for extra projection supports ..                                                                                                  | C.ft. | 5 0 0     | 92'14    |
| 13   | Teakwood doors $1\frac{1}{2}$ " thick battened shutters all necessary iron fixtures complete ..                                                                                                       | S.ft. | 1 4 0     | 156      |
| 14   | Teakwood windows with 3" x 4" frame $1\frac{1}{2}$ " thick battened shutters 5/8" dia. iron bars 4" apart and all necessary iron fixtures, etc., complete ..                                          | S.ft. | 1 6 0     | 75       |
| 15   | Teakwood wall shelves 3" x 4" frame work with $1\frac{1}{2}$ " thick battened shutters and $\frac{3}{4}$ " cross planks, etc., complete ..                                                            | S.ft. | 1 2 0     | 60       |
| 16   | Chocolate painting 2 coats (mixed and applied as per Bombay specifications) ..                                                                                                                        | Sqr.  | 3 0 0     | 6'00     |
| 17   | Constructing sinks in bath rooms (Brick in mortar and flooring with chunam jelly and cement concrete plastering with cement mortar etc., complete—walls $1\frac{1}{2}$ ' high)..                      | No.   | 5 0 0     | 4        |
| 18   | Providing and fixing stone mortar and pestle ..                                                                                                                                                       | "     | 5 0 0     | 4        |
| 19   | Flooring with cement concrete 1:2:4 to $1\frac{1}{2}$ " thick on a bed of 6" thick lime concrete with topping of red cement $\frac{3}{4}$ " thick finished and cut to required pattern when required. | Sqr.  | 20 0 0    | 8'00     |
| 20   | Levelling ground and clearing site and other unforeseen works,                                                                                                                                        | L.S.  | ..        | ..       |

Notification dated 15th August 1939.

Notice is hereby given that sealed tenders will be received at the Office of the Executive Engineer, Tumkur Division, up to 2 P.M. on 9th September 1939, for constructing four units of latrine at

Tiptur Town. An approximate estimate of quantities is given below. These quantities are not guaranteed. The work should be completed by the end of December 1939.

2. The plans, detailed estimate and conditions may be seen at the Executive Engineer's Office at Tumkur, between the hours of 11 A.M. and 5 P.M.

3. Tenders should be submitted on printed forms, which may be obtained by paying Re. 0-4-0 from the Executive Engineer. The tenders should be accompanied by a statement in the form given below, showing the rates at which the different items specified will be executed.

4. Each tender must be accompanied by a treasury chellan for Rs. 20 for having credited to '17(a) P. W. Deposits' as earnest money, and be accompanied by a tender for constructing four units of latrine at Tiptur Town in default of which tenders will be rejected.

5. The final acceptance of any tender will rest with the Executive Engineer. He does not bind himself to accept the lowest or any tender or to assign any reason whatsoever for the rejection of any tender.

6. Within eight days of the acceptance of the tender, the successful competitor will furnish to the Executive Engineer a contract bond, in default of which his tender will be considered as forfeited and his earnest money will be forfeited.

7. The name of the successful competitor, whose tender has been accepted, will be posted on the Notice Board in the Executive Engineer's Office in due course. No enquiry regarding the acceptance or rejection of a tender will receive any reply.

8. In the case of one of the tenders, the earnest money on rejected tenders will be returned.

9. Rates once tendered will not be enhanced on any account.

10. Rates for non-tendered items estimated from data will be as per schedule rates of the department or those fixed by the Executive Engineer after working out data with not more than 10 per cent for contractor's profit.

11. In all matters of specification, prices and in all matters of dispute about rates, quantities, measurements, quality of work, etc., the decision of the Executive Engineer will be final and binding on the contractor.

12. Quotations must be given in rupees as well as in paise and they must be in specific terms of unit shown against each item of work. Any quotation quoted at so much percentage less or more than estimated rate will not be accepted.

Approximate estimate for constructing one unit of Latrine for the Electrical Department, Tiptur Town.

| No. | Description of work                                                                                                                    | Per     | Rate      | Quantity |
|-----|----------------------------------------------------------------------------------------------------------------------------------------|---------|-----------|----------|
| 1   | Earthwork excavation for pit 4' x 4' x 4'                                                                                              | Cyd     | Rs. 2 3 6 | 4        |
| 2   | Burnt brick masonry for walls and floor of pit, 4' x 4' x 4', with bond course of 1' apart in every course for foundation and basement | Sq. ft. | 0 3 6     | 100      |
| 3   | Burnt brick in mortar for superstructure                                                                                               | Sq. ft. | 0 4 6     | 100      |
| 4   | Chunam plastering                                                                                                                      | Sq. ft. | 3 0 0     | 5-60     |
| 5   | Cement pointing basement allround                                                                                                      | Sq. ft. | 3 8 0     | 0-56     |
| 6   | Wash and colour washing 2 coats                                                                                                        | Sq. ft. | 0 4 6     | 5-56     |
| 7   | Cement plastering 1/2" thick allround                                                                                                  | Sq. ft. | 7 0 0     | 0-79     |
| 8   | Tar washing 2 coats                                                                                                                    | Sq. ft. | 1 2 0     | 0-63     |
| 9   | Flooring with cement plaster 1" thick                                                                                                  | Sq. ft. | 12 0 0    | 0-56     |
| 10  | Fixing outlet for water                                                                                                                | L. S.   |           |          |
| 11  | Supplying galvanized iron sheet for roof complete with painting                                                                        | No.     | 1 0 0     | 1        |
| 12  | Unforeseen charge                                                                                                                      | L. S.   |           |          |

Notification dated 15th August 1939.

Notice is hereby given that sealed tenders will be received at the Office of the Executive Engineer, Tumkur Division, up to 2 P.M. on 9th September 1939, for constructing one double block of Operators' Quarters at Tiptur. An approximate estimate of quantities is given below. These quantities are not guaranteed. The work should be completed by the end of December 1939.

2. The plans, detailed estimate and conditions may be seen at the Executive Engineer's Office at Tumkur, between the hours of 11 A.M. and 5 P.M.

3. Tenders should be submitted on printed forms which may be obtained by paying Re. 2-0-0 from the Executive Engineer. The tenders should be accompanied by a statement in the form given below, showing the rates at which the different items specified will be executed.

4. Each tender must be accompanied by a treasury chellan for Rs. 175 credited to '17(a) P. W. Deposits' as earnest money and be accompanied by a tender for constructing one double block of Operators' Quarters at Tiptur in default of which tenders will be rejected.

5. The final acceptance of any tender will rest with the Executive Engineer, who does not bind himself to accept the lowest or any tender or to give any reason whatever for the rejection of any tender.

6. Within eight days of the acceptance of the tender, the successful competitor will be required to execute the usual contract bond, in default of which his tender will be considered cancelled and his earnest money will be forfeited.

7. The name of the successful competitor, whose tender has been accepted, will be posted on the Notice Board in the Executive Engineer's Office in due course. No enquiry regarding the acceptance or rejection of a tender will receive any reply.

8. On acceptance of one of the tenders, the earnest money on rejected tenders will be returned.

9. Rates once tendered will not be enhanced on any account.

10. Rates for non-tendered and non-estimated items shall be as per schedule rates of the department or those fixed by the Executive Engineer after working out data with not more than 10 per cent for contractor's profit.

11. In all matters not specifically provided for and in all matters of dispute about rates, quantities, measurements, quality of works, etc., and in all disputes of any kind, the decision of the Executive Engineer will be final and legally binding.

12. Quotations must be given in words as well as in figures and they must be in specific term of unit shown against each item of work. Any quotation quoted at so much percentage less or more than estimated rate will not be accepted.

Abstract of estimate for one unit of Double Block of Operators' Quarters for Electrical Department in Tiptur Town.

| No. | Description of work                                                                                                                                                                         | Per   | Rate      | Quantity |
|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-----------|----------|
|     |                                                                                                                                                                                             |       | Rs. a. p. |          |
| 1   | Earthwork excavation in gravelly soil and filling in basement including watering and tamping in layers 6" thick                                                                             | C.yd. | 0 3 6     | 53       |
| 2   | Stone jelly (1" size) concrete in lime mortar 1 : 2 : 4 for foundations laid in 4" layers and well tamped                                                                                   | C.ft. | 0 3 6     | 597      |
| 3   | Burnt size stone in clay in courses not less than 8" high with bond stones 6' apart in every course for foundations and for basement including all quoins neatly dressed 2" wide at corners | "     | 0 3 6     | 1,079    |
| 4   | Burnt brick in clay for superstructure                                                                                                                                                      | "     | 0 3 0     | 1,946    |
| 5   | Burnt brick in lime mortar for superstructure                                                                                                                                               | "     | 0 4 6     | 746      |
| 6   | Burnt stone slabs 6" thick set in mortar with two line dressing for steps and all exposed faces etc., complete                                                                              | S.ft. | 0 5 0     | 249      |
| 7   | Teakwood doors with 3" x 4" frame 1 1/4" thick battened shutters and all necessary iron fixtures complete                                                                                   | "     | 1 4 0     | 280      |
| 8   | Teakwood windows with 3" x 4" frame 1 1/4" thick battened shutters 3/8" dia. iron bars 4" apart and all necessary iron fixtures, etc., complete                                             | "     | 1 6 0     | 116      |
| 9   | Teakwood wall shelves 3" x 4" frame work with 1 1/4" thick battened shutters and 3/4" cross planks and all necessary iron fixtures with locking arrangements, etc., complete                | "     | 1 2 0     | 96       |
| 10  | Teakwood wrought and put up with wood oiling 2 coats, etc., complete                                                                                                                        | C.ft. | 5 0 0     | 85.5     |
| 11  | Teakwood eave boards plain 9" deep 3/4" thick fixing complete                                                                                                                               | R.ft. | 0 9 0     | 149      |
| 12  | Roofing with 1st Class Mangalore tiles on teak reapers nailed including wood oiling to reapers eave tiles being tied by a teak batter                                                       | Sqr.  | 25 0 0    | 15.00    |
| 13  | Mangalore ridge tiles set in mortar and cement pointed                                                                                                                                      | R.ft. | 0 8 0     | 78       |
| 14  | Tested rolled steel girders as per B.S.S. including lifting and hoisting with 2 coats of approved paint with necessary clamps, etc., complete                                               | Cwt.  | 12 0 0    | 6.36     |
| 15  | Boxing girders with cement concrete                                                                                                                                                         | R.ft. | 0 10 0    | 20       |
| 16  | Roofing with Madras terrace filled in with brick in surki mortar with 3 courses of flat tiles surface and ceiling plastered with chunam etc., complete                                      | Sqr.  | 30 0 0    | 3.62     |
| 17  | Plain parapet wall with cement brick in mortar 9" thick 1 1/4" to 2 1/4" high including blocking course 6" high with deep holes 8" apart including plastering with chunam mortar            | R.ft. | 0 10 0    | 60       |
| 18  | Burnt brick in mortar cornice 9" deep with 6" projection as per design including chunam plastering                                                                                          | "     | 0 9 0     | 63       |
| 19  | Flooring with cement concrete 1 : 2 : 4 to 1 1/2" thick on a bed of 6" thick lime concrete with topping of red cement 3/8" thick finished and cut to required pattern when required         | Sqr.  | 20 0 0    | 9.00     |

| No. | Description of work                                                                       | Per   | Rate      | Quantity |
|-----|-------------------------------------------------------------------------------------------|-------|-----------|----------|
|     |                                                                                           |       | Rs. a. p. |          |
| 20  | Chunam plastering 2 coats including rounding off corners and smooth rendering             | Sqr.  | 0 0 0     | 50       |
| 21  | Cement pointing with fibred lime after scraping the surface to 1" to 1 1/2" deep          | "     | 0 0 0     | 2-21     |
| 22  | White and colour washing 2 coats                                                          | "     | 0 0 0     | 2-21     |
| 23  | Rainwater down pipe 4" dia. including suitable girths mouth at top and bottom             | Rd.   | 0 0 0     | 2        |
| 24  | Wire bands 1/4" dia. for 4" x 4" including plastering concrete                            | "     | 0 0 0     | 2        |
| 25  | Chocolate paint 2 coats and applied as per Bombay Specifications                          | Sqr.  | 0 0 0     | 2        |
| 26  | Expanded metal 1/2" dia. mesh for frame work including door and window openings complete. | S.ft. | 0 0 0     | 133      |
| 27  | Constructing chimney 2 feet high                                                          | No.   | 0 0 0     | 2        |
| 28  | Constructing 2 feet high                                                                  | "     | 0 0 0     | 2        |
| 29  | Founding and lifting 2 feet high                                                          | "     | 0 0 0     | 2        |
| 30  | Leveling ground and other unforeseen charge                                               | L. S. | ..        | ..       |

Notation dated 14th August 1939.

Notice is hereby given that work will be received at the Office of the Executive Engineer Tumkur Division, up to 10th September 1939 for constructing one block of Officer's Quarters at Tiptur. An approximate estimate of work is given below. These quantities are not guaranteed. The work should be completed by the end of December 1939.

2. The plans, detailed estimate and conditions may be seen at the Executive Engineer's Office at Tumkur between the hours of 11 A.M. and 5 P.M.

3. Tenders should be submitted on printed forms which may be obtained by paying Rs. 1-3 from the Executive Engineer. The tenders should be accompanied by a statement in the form given below showing the rates at which the different items specified will be executed.

4. Each tender must be accompanied by a treasury cheques for Rs. 150 credited to P. V. Deposits, Government money, and be superscribed "Tender for constructing one block of Officer's Quarters at Tiptur, in default of which, tender will be rejected.

5. The acceptance of any tender will not bind the Executive Engineer who does not bind himself to accept the lowest or any tender nor to assign any reason with or without objection of any tender.

6. Within eight days of the acceptance of the tender the successful competitor will be required to execute the usual contract bond, in default of which, tender will be considered cancelled and his earnest money will be forfeited.

7. The name of the successful competitor, whose tender has been accepted, will be posted on the Notice Board in the Executive Engineer's Office in due course. No enquiry regarding the tender or rejection of a tender will receive any reply.

8. The amount of any of the tenders the earnest money on rejected tenders will be returned.

9. Rejected tenders will not be enhanced on any account.

10. Rejected tenders will be considered and non-estimated items shall be at per schedule rates of the Department and 10% of the Executive Engineer after working out data with not more than 10 per cent of the estimated price.

11. In all matters not specifically provided for and in all matters of dispute of quantities, measurements, quality of materials and in all disputes of any kind, the decision of the Executive Engineer will be final and binding.

12. Quantities must be given in words, as well as in figures and they must be in specific terms of unit shown against each item of work. Any quotation quoted at so much percentage less or more than the estimated rate will not be accepted.

Abstract estimate for construction of one block of Officer's Quarters for the Tiptur Division in Tiptur Town.

| No. | Description of work                                                                                                     | Rate      | Quantity |
|-----|-------------------------------------------------------------------------------------------------------------------------|-----------|----------|
|     |                                                                                                                         | Rs. a. p. |          |
| 1   | Barthwork excavation                                                                                                    | Cyd       | 59       |
| 2   | Stone jelly concrete 1:2:4 in chunam mortar                                                                             | C.ft.     | 454      |
| 3   | Stone jelly in lime mortar foundation and basement including 6 feet apart in courses not less than 8" thick and 2" wide | "         | 1,372    |

| No. | Description of work                                                                                                                                         | Per   | Rate               | Quantity |
|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|--------------------|----------|
| 4   | Burnt brick in clay superstructure                                                                                                                          | C.ft. | Rs. a. p.<br>0 3 0 | 1,982    |
| 5   | Burnt brick in lime mortar for dies of doors and windows                                                                                                    | "     | 0 4 6              | 215      |
| 6   | Burnt stone slabs 6" thick for cills and lintels for doors, windows and steps, etc.                                                                         | S.ft. | 0 5 0              | 278      |
| 7   | Teakwood doors with 3"×4" frame battened shutters of 1½" thick with iron fittings, etc., complete                                                           | "     | 1 4 0              | 163      |
| 8   | Teakwood windows 3"×4" frames ½" battened shutters ¾" dia., iron bars 4" apart, etc., complete with iron fitting                                            | "     | 1 6 0              | 110      |
| 9   | Wall shelves 3"×4" frame 1½" shutters with ¾" planks and iron fittings, etc., complete                                                                      | "     | 1 2 0              | 48       |
| 10  | R.S. joist for verandah                                                                                                                                     | Cwt.  | 13 0 0             | 4.7      |
| 11  | Boxing girders with cement concrete and plates, etc., complete.                                                                                             | R.ft. | 0 6 0              | 25       |
| 12  | Teakwood wrought and put up with two coats of wood oiling, etc., complete                                                                                   | C.ft. | 5 0 0              | 60       |
| 13  | Roofing with 1st class Mangalore tiles on Teakwood reepers and wood oiling to reepers eave tiles being fixed by teak batten                                 | Sqr.  | 25 0 0             | 10.50    |
| 14  | Mangalore ridge tiles set in mortar                                                                                                                         | R.ft. | 0 8 0              | 68       |
| 15  | Teakwood eave boards 9" wide ¾" thick fixing, etc., complete                                                                                                | "     | 0 9 0              | 148      |
| 16  | Roofing with pucca Madras terrace with brick on edge 3" surki concrete with 3 courses of flat tiles including plastering, etc., complete                    | Sqr.  | 30 0 0             | 2.71     |
| 17  | Ventilating tiles double                                                                                                                                    | No.   | 4 0 0              | 8        |
| 18  | Parapet wall 1½ to 2 feet height including plastering, etc., complete 9" thick with blocking course 6" high and deep holes 8 feet apart                     | R.ft. | 0 10 0             | 47       |
| 19  | Chunam mortar plastering 2 coats including rounding corners, etc., complete                                                                                 | Sqr.  | 3 0 0              | 33.24    |
| 20  | White and colour washing                                                                                                                                    | "     | 0 4 6              | 34.00    |
| 21  | Flooring with 1½" cement concrete 1:2:4 and 6" thick lime concrete and ½" cement plastering mixed with red cement and cut into tile pattern, etc., complete | "     | 20 0 0             | 8.14     |
| 22  | Putting cornice to terrace portion 6" wide                                                                                                                  | R.ft. | 0 6 0              | 47       |
| 23  | Chocolate painting 2 coats                                                                                                                                  | Sqr.  | 3 0 0              | 7.85     |
| 24  | Rainwater down zinc pipes 4" dia., including suitable bell-mouth at top and bent at bottom, etc.                                                            | R.ft. | 0 8 0              | 48       |
| 25  | Constructing chimney in kitchen and bath                                                                                                                    | No.   | 50 0 0             | 2        |
| 26  | Constructing sinks 1½' high with cement concrete and plastering, etc., complete                                                                             | "     | 5 0 0              | 2        |
| 27  | Providing and fixing postle and mortar                                                                                                                      | Each  | 5 0 0              | 1        |
| 28  | Expanded metal frame 3"×1½" mesh with teak frame including door of iron fittings, etc., complete                                                            | S.ft. | 0 12 0             | 116      |
| 29  | Levelling ground and clearing site, etc.                                                                                                                    | L. S. |                    |          |

Notification dated 15th August 1939.

Notice is hereby given that sealed tenders will be received at the Office of the Executive Engineer, Tumkur Division, up to 2 P.M. on 9th September 1939, for constructing combined Office and Stores Building at Tiptur Town. An approximate estimate of quantities is given below. These quantities are not guaranteed. The work should be completed by the end of December 1939.

2. The plans, detailed estimate and conditions may be seen at the Executive Engineer's Office at Tumkur, between the hours of 11 A.M. and 5 P.M.

3. Tenders should be submitted on printed forms which may be obtained by paying four annas from the Executive Engineer. The tenders should be accompanied by a statement in the form given below, showing the rates at which the different items specified will be executed.

4. Each tender must be accompanied by a Treasury challan for Rs. 120 credited to '17 (a) P. W. Deposits,' as earnest money, and be superscribed "Tender for constructing combined Office and Stores Building" at Tiptur, in default of which tenders will be rejected.

5. The final acceptance of any tender will rest with the Executive Engineer, who does not bind himself to accept the lowest or any tender or to assign any reason whatever for the rejection of any tender.

6. Within eight days of the acceptance of the tender, the successful competitor will be required to execute the usual contract bond, in default of which his tender will be considered cancelled and his earnest money will be forfeited.

7. The name of the successful tenderer, whose tender has been accepted, shall be printed in the Notice Board in the Executive Engineer's Office in due course. No enquiry regarding the acceptance or rejection of a tender will be entertained.

8. On acceptance of one of the tenders, the money on rejected tenders will be returned.

9. Rates once tendered will not be enhanced or reduced.

10. Rates for non-tendered and non-estimated items shall be as per schedule rates of the department or those fixed by the Executive Engineer after working out data with not more than 10 per cent for contractor's profit.

11. In all matters not specifically provided for and in all matters of dispute about rates, quantities, measurements, quality of works, etc., and in all disputes of any kind the decision of the Executive Engineer shall be final and binding.

12. Quotations must be given in words as well as in figures and specify in detail in specific term of unit shown against each item of work. Any quotation quoted at more than 10 per cent less or more than estimated rate will not be accepted.

Abstract estimate for constructing Combined Station Office and Store building for District Department at Tiptur Town.

| No. | Description of work                                                                                                                                                                    | Per   | R      | Q     |  |
|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|--------|-------|--|
| 1   | Earthwork in filling heavy soil and filling in basement including concrete and 2" layer in layers 6" thick                                                                             | Cyd.  | 0 2 1  |       |  |
| 2   | Stone masonry in foundation 1' x 1' x 4' foundations and 1' x 1' x 1' foundations                                                                                                      | Cf.   |        |       |  |
| 3   | Stone masonry in wall not less than 8" high with bond stone in half the wall for foundations and for basement including 2" wide at corners                                             |       | 3      | 869   |  |
| 4   | Burnt brick in wall for superstructure                                                                                                                                                 |       | 0 0    | 1,298 |  |
| 5   | Burnt brick in wall for superstructure                                                                                                                                                 |       | 6 5 6  | 111   |  |
| 6   | Plaster in wall with 1" lime mortar with two line dressing for corners and one line dressing for straight line                                                                         | S.ft. | 0 5 0  | 177   |  |
| 7   | Stone masonry in wall one line dressed and set in mortar                                                                                                                               |       | 0 4 0  | 7     |  |
| 8   | Burnt brick in wall 1' x 1' square and 1' x 9" high including plaster and cement plastering 1/2"                                                                                       | N.    |        |       |  |
| 9   | Cement plastering 1/2" including rounding off corners and smooth rendering                                                                                                             | Sq.   | 0 0    | 29.00 |  |
| 10  | Cement plastering with 1/2" lime after scraping the joints to 1/2" deep                                                                                                                |       |        |       |  |
| 11  | White wash on wall as per plastering and painting                                                                                                                                      |       |        |       |  |
| 12  | Burnt brick in wall 1' x 1' square and 1' x 6" projection as per design including plaster and cement plastering                                                                        | R.ft. | 0 9 0  | 17    |  |
| 13  | Plain parapet wall 1' x 1' square and 1' x 1' thick 1 1/2' to 2 1/2' high including plaster and cement plastering 1/2" deep holes 8 feet apart including plaster and cement plastering | R.ft. |        | 17    |  |
| 14  | Chimney in wall 1' x 1' square and 1' x 1' thick                                                                                                                                       | N.    |        |       |  |
| 15  | Chimney in wall 1' x 1' square and 1' x 1' thick                                                                                                                                       | N.    |        |       |  |
| 16  | Stone masonry in wall 1' x 1' square and 1' x 1' thick including plaster and cement plastering 1/2" deep holes 8 feet apart including plaster and cement plastering                    | Sq.   | 20 0 0 | 6.00  |  |
| 17  | Roofing and ceiling in room with terrace bricks on edge filled with concrete and mortar with three courses of flat tiles including plaster and cement plastering, etc., complete       |       | 30 0 0 | 6.24  |  |
| 18  | Tested R.R. steel girder 1' x 1' square including lifting and hoisting with 2" x 1" x 1" x 1" with necessary clamps, etc., complete                                                    | Cwt.  | 14 0 0 | 18.5  |  |
| 19  | Teakwood joist 15" x 15" centre to centre with 1" coat of woodoil, etc., complete                                                                                                      | C.ft. | 5 0 0  | 53.0  |  |
| 20  | Teakwood door with 3' x 3' frame work 1 1/2" thick including 4 hold-fasts of flat-iron 15" x 12" x 1/2" iron fittings, Reindoor locks with handles, etc., complete                     | S.ft. | 1 6 0  | 92    |  |
| 21  | Teakwood window with glazed shutters 1 1/2" thick with iron bars 1/2" dia. 4" apart with necessary iron fittings, etc., complete in four halves                                        |       | 1 10 0 | 70    |  |
| 22  | Teakwood ventilators fully glazed with iron bars, etc., complete                                                                                                                       |       | 1 4 0  | 27    |  |

| No. | Description of work                                                                                                                      | Per   | Rate      | Quantity |
|-----|------------------------------------------------------------------------------------------------------------------------------------------|-------|-----------|----------|
|     |                                                                                                                                          |       | Rs. a. p. |          |
| 23  | Chocolate painting 2 coats (mixed and applied as per Bombay specifications)                                                              | Sq.   | 3 0 0     | 12.87    |
| 24  | Fixing with wire gauge shutters with teakwood reepers, etc., complete                                                                    | S ft. | 1 4 0     | 63       |
| 25  | Rainwater down zinc pipes, 4" dia., including suitable bell-mouth at top and bend at bottom                                              | R.ft. | 0 8 0     | 78       |
| 26  | Brick in lime mortar and stone slabs with chunam plastering, etc., complete for brackets                                                 | L. S. |           |          |
| 27  | Clearing site and levelling ground, etc.                                                                                                 | "     |           |          |
| 28  | Boxing girders 12×5 with cement-concrete with wire netting and plastering with chunam mortar, etc., complete                             | R.ft. | 0 8 0     | 30       |
| 29  | Boxing double joists verandah with brick in mortar inside and cement concrete outside with wirenet casing and plastering, etc., complete | "     | 0 8 0     | 40       |
| 30  | Binding wall over terrace on cross wall 9"×9" with plastering, etc., complete                                                            | "     | 0 4 0     | 16       |

*Notification dated 18th August 1939.*

Notice is hereby given that, sealed tenders will be received at the office of the Executive Engineer, Tumkur Division, up to 2 P.M., on 9th September 1939, for restoration of Garugada Kuppe, Urmundinkere belonging to Sri Anjaneyaswami Temple of the said village, Tumkur Taluk. An approximate estimate of quantities is given below. These quantities are not guaranteed. The work should be completed by the end of December 1939.

2. The plans, detailed estimate and conditions may be seen at the Executive Engineer's Office at Tumkur, between the hours of 11 A.M. and 5 P.M.

3. Tenders should be submitted on printed forms which may be obtained on payment of 4 annas for each form from the Executive Engineer. The tenders should be accompanied by a statement in the form given below, showing the rates at which the different items specified will be executed.

4. Each tender must be accompanied by a Treasury chellan for Rs. 210 only credited to 17 (a) P. W. Deposits, as earnest money, and be superscribed "Tender for restoring Jodi Garugadakuppe Urmundinkere, Tumkur Taluk," in default of which tenders will be rejected.

5. The final acceptance of any tender will rest with the Executive Engineer, who does not bind himself to accept the lowest or any tender or to assign any reason whatever for the rejection of any tender.

6. Within eight days of the acceptance of the tender, the successful competitor will be required to execute the usual contract bond, in default of which his tender will be considered cancelled, and his earnest money will be forfeited.

7. The name of the successful competitor, whose tender has been accepted, will be posted on the Notice Board in the Executive Engineer's Office in due course. No enquiries regarding the acceptance or rejection of a tender will receive any reply.

8. On acceptance of one of the tenders, the earnest money on rejected tenders will be returned.

9. Rates once tendered will not be enhanced on any account.

10. Rates for non-tendered and non-estimated items shall be as per current schedule rates of the department or those fixed by the Executive Engineer after working out data with not more than 10 per cent for contractor's profit.

11. In all matters not specifically provided for and in all matters of dispute about rates, quantities, measurements, quality of works, etc., and in all disputes of any kind, the decision of the Executive Engineer will be final and legally binding.

12. Quotations must be given in words as well as in figures and they must be in specific term of unit shown against each item of work. Any quotation quoted at so much percentage less or more than estimated rate will not be accepted.

Abstract estimate for restoring Jodi Garugadakuppe Urmundinkere Tank, Serial No. 623, Tumkur Taluk.

| No. | Details of work                                                          | Per   | Rate      | Quantity |
|-----|--------------------------------------------------------------------------|-------|-----------|----------|
|     |                                                                          |       | Rs. a. p. |          |
|     | BUND.                                                                    |       |           |          |
| 1   | Clearing jungle with roots and removing ant hills                        | Grade | 1 0 0     | 22       |
| 2   | Cutting longitudinal grips at top and in rear slope (four in each grade) | "     | 2 8 0     | 22       |

| No.                                  | Details of work                                                                               | Per   | Rate      | Quantity |
|--------------------------------------|-----------------------------------------------------------------------------------------------|-------|-----------|----------|
|                                      |                                                                                               |       | Rs. a. p. |          |
| 3                                    | Clearing foundation silt for new bund portion                                                 | Cyd.  | 0 2 0     | 198      |
| 4                                    | Earthwork to bund with watering and consolidation (soil from draft clearing from weir)        | "     | 0 4 0     | 673      |
| 5                                    | Earthwork to bund with watering and consolidation (for old bund)                              | "     | 0 3 6     | 4,605    |
| 6                                    | Carrying the earth from approach clearing and consolidating the same                          | "     | 0 2 2     | 1,200    |
| 7                                    | Turning (rear slope)                                                                          | S.yd. | 0 9 0     | 1,200    |
| 8                                    | Paddle wall for the new bund at left end                                                      | Cyd.  | 0 12 0    | "        |
| 9                                    | Rough stone work new with lead                                                                | "     | 1 12 0    | "        |
| 10                                   | Rough stone work—old—resetting the disturbed revetment                                        | "     | 0 12 0    | "        |
| 11                                   | Providing and fixing grade stones including cutting figures and painting                      | No.   | 2 0 0     | 23       |
| 12                                   | Setting Index stones including the dressing at top                                            | "     | 0 8 0     | 23       |
| 13                                   | Providing and fixing B.M. stones in facing figuring and painting                              | "     | 4 0 0     | 2        |
| 14                                   | Do Reg. No. and date stone                                                                    | "     | 4 0 0     | 1        |
| 15                                   | Do Gauge stone                                                                                | "     | 17 0 0    | 1        |
| 16                                   | Miscellaneous works for the protective works at the drinking water wells at the right end     | L. S. |           |          |
| SLUICE AT R.L. 45.50,                |                                                                                               |       |           |          |
| 1                                    | Earthwork excavation cutting open bund and refilling the same with watering and consolidation | Cyd.  | 0 3 0     | 74       |
| 2                                    | Laying broken jelly concrete in surki mortar                                                  | C.ft. | 0 4 0     | 158      |
| 3                                    | Burnt brick in surki mortar                                                                   | "     | 0 4 6     | 289      |
| 4                                    | Burnt stone slabs 6" thick roughly dressed and fixed                                          | S.ft. | 0 6 0     | 244      |
| 5                                    | Plastering with surki mortar                                                                  | Sqr.  | 3 8 0     | 302      |
| 6                                    | Cutting holes in 6" thick slabs                                                               | No.   | 1 0 0     | 1        |
| 7                                    | Cost of C.I. pipes of 6" dia., including conveying and fixing, et                             | R.ft. | 3 0 0     | 36       |
| 8                                    | Providing wooden pile with iron rod and locking arrangement                                   | L. S. |           |          |
| 9                                    | Refilling the excavated earth with watering and consolidation                                 | Cyd.  | 0 2 0     | 74       |
| 10                                   | Closing the deal in the bund at old sluice site                                               | L. S. |           |          |
| WASTE WEIR 148' LONG AT R. L. 52.00. |                                                                                               |       |           |          |
| 1                                    | Approach and draft clearing in hard gravelly soil to R.L. 52.00                               | Cyd.  | 0 3 6     | 1,200    |
| 2                                    | Broken jelly concrete in surki mortar                                                         | C.ft. | 0 4 0     | 241      |
| 3                                    | Burnt brick in surki mortar                                                                   | "     | 0 4 6     | 287      |
| 4                                    | Burnt stone slabs dressed and fixed coping with return and steps (6" thick)                   | S.ft. | 0 6 0     | 171      |
| 5                                    | Cutting joggle joints                                                                         | No.   | 0 12 0    | 0        |
| 6                                    | Rough stone revetment new with 2 1/2 miles lead                                               | Cyd.  | 1 12 0    | 35       |
| 7                                    | Removing and refixing the disturbed old weir apron                                            | "     | 0 12 0    | 35       |

P. RAJAGOPALAN,  
Executive Engineer.

#### OFFICE OF THE ASSISTANT ENGINEER, HEADQUARTER RANGE, MYSORE

Notification dated 16th August 1939.

1. Sealed tenders will be received at the Office of the Assistant Engineer, Headquarter Range, Mysore, up to 2 p.m. on 4th September 1939, for constructing a building for Advanced Cases Ward, P. K. Sanatorium, Mysore.

2. Tenders in the prescribed form obtainable from the Office of the Assistant Engineer, Headquarter Range, Mysore, on payment of four annas for each form, should be addressed to the Assistant Engineer, Headquarter Range, and should be superscribed as "Tender for constructing a building for Advanced Cases Ward in P. K. Sanatorium, Mysore." The name of the tenderer should also be superscribed on the sealed cover.

3. Each tender must be accompanied by a deposit of Rs. 500 only in cash (at cash payment value at the time of deposits and not face value), as earnest money. The earnest money of the successful

tenderer will be retained as cash security for the due fulfilment of the contract. (Cash amount will not carry any interest.) The amount of earnest money should be paid direct to treasury and the duplicate treasury challan submitted separately along with the tender.

4. The tenders will be opened in the presence of such tenderers who wish to be present on 4th September 1939 at 4 P.M. The final acceptance of the tender will rest with the Superintending Engineer who does not bind itself to accept the lowest or any tender, or to assign any reasons whatever for the rejection of any.

5. The name of the successful tenderer will be posted on the Notice Board in the Assistant Engineer's Office in due course. Within eight days of the acceptance of the tender, the successful tenderer will be required to execute the agreement in the departmental schedule contract form for the due fulfilment of the contract.

6. Failure to comply with the condition 5 above or to agree to carry out the work in accordance with the specifications and agreements in force will entail forfeiture of the earnest money.

7. Copies of contract documents, estimates and drawings may be seen at any time at the Office of the Assistant Engineer, Headquarter Range, Mysore, on all working days, between 11 A.M. and 5 P.M.

8. Specific rates should be given for each item in the schedule and the rates should be in rupees, annas and in multiples of three pies and expressed in words and figures.

9. Any rates or lumpsum amounts for the items not called for, if tendered by the tenderer, will not be taken notice of. The rates tendered should include all such lumpsum items.

10. No alterations which are made by the tenderers in the contract documents in the nomenclature of the sanctioned sub-heads will be recognised and if corrections are made, the tenders will be liable to rejection.

11. There should be no corrections or erasures in the tenders in the rates of items and any corrections made in the rates should be attested to and the number of corrections, if any, in each page noted at the foot of the same by the tenderer.

12. No reference should be made to the Public Works Department current schedule of rates.

13. On the event of the tender being submitted by a firm, it must be signed separately and severally by each member thereof or in the event of absence of any partner, it must be signed on his behalf by a person holding power-of-attorney authorising him to do so.

14. When once the rates tendered have been accepted, they will not be revised under any circumstances. In regard to items of work not tendered, the rates to be proposed by the Assistant Engineer, Headquarter Range, Mysore, and approved by the Superintending Engineer shall be final and legally binding on the tenderer.

15. The quantities as estimated are only approximate and are liable to alterations, omissions, deductions or additions, at the discretion of the Assistant Engineer or his representative. The tendered rates will hold good for any quantity whether higher or lower than those estimated for.

16. The work should be completed as per departmental specifications for different items and handed over to the Public Works Department within three months from the date of issue of order for the commencement of the work failing which the Assistant Engineer may, at his discretion, levy a penalty up to Rs. 10 per day of delay which will be recovered from the contractor's outstandings for the period exceeded by him till the work is completed and handed over.

17. In all matters of dispute of any kind, not specially provided for in the agreement or of rates, penalties, measurements, quality of work, etc., the decision of the Chief Engineer shall be final and legally binding.

18. The earnest money of rejected tenders will be returned on surrender of the receipts originally granted, along with an application to the Assistant Engineer, Headquarter Range, Mysore.

19. No claims for damages for delays caused by officers of the department in the execution of the work will be considered, whatever may be the reason for such delays. Contractors should bear this in mind when tendering for work. Extension of time due to delays caused by the departmental officers will, however, be considered on the merits of each case.

20. The contract should not be sublet.

21. All materials, tools, plant and machinery that will be supplied by the Assistant Engineer in the interest of the work, shall be accepted by the tenderer at the rates fixed by the Assistant Engineer and the tenderer will pay the hire, etc., on machinery at the prescribed per cent per annum of the booked value of the tools and plant supplied from the date of taking over of tools and plant from the Stores to the date of return to the Stores, the dates considered being the dates of acknowledgments of the vouchers in each transaction.

22. The contractor should arrange for the payment of royalty and tolls.

Note.—(a) The contractor should at his own cost—

- (1) Provide rods, stakes, ropes and labours required in setting out the works.
- (2) Provide all necessary scaffolding, centering, labour and appliances for hoisting.
- (3) Provide mortar mill and shed to keep materials under cover and also for workmen.
- (4) Arrange for protecting work during inclement weather.
- (5) Supply requisite temporary lights, water cisterns, water-shoots, coverings to masonry, tile pieces to steps, sieves, parabs, or measures, shoring and other requisite protection during the progress of the work.
- (6) Supply all water required for work and workmen and shall provide latrines, drainages, etc.
- (7) Clean away all dirt, rubbish, superfluous materials and debris as they accumulate.
- (8) Provide arrangements for pumping and bailing from excavations and foundations, wherever and whenever necessary with their own pumping apparatus including necessary leading drains, slump pits, etc.

- (9) Wash floors at completion and leave the whole of the work and premises in a clean and orderly condition, etc.
- (10) Afford facilities to any other parties employed upon the work so that their work may proceed during the progress of the contract, and give such persons the use of ordinary scaffolding and ladders.
- (b) It is the business of the contractors to make their own arrangements for the quarries and supplies of materials.
23. The rates for woodwork for all works quoted should be based on the rates of the departmental supply as noted below. Only Mysore teak selected from the Mysore Government Depots must be used.
24. Work to the extent of Rs. 6,000 will have to be carried out each month.

Prevailing Government rates at Mysore Forest Depot for Mysore teak is as follows:—

|      |                                    |    |    | Rs. | a. | p. |             |
|------|------------------------------------|----|----|-----|----|----|-------------|
| (1)  | Selected 1st class logs            | .. | .. | ..  | 2  | 8  | 0 per c.ft. |
| (2)  | Cut scantling of sizes 3"×4"       | .. | .. | ..  | 3  | 4  | 0 "         |
| (2a) | Do 3"×5" to 4"×7"                  | .. | .. | ..  | 3  | 12 | 0 "         |
| (3)  | Planks 1" to 1½" to required sizes | .. | .. | ..  | 4  | 8  | 0 "         |

25. Only Chamundi Brand cement should be used for all works requiring this nature.
26. Such of the tenders which do not clearly quote with detailed specifications for all the items without exception will not be considered.

Abstract estimate for constructing an Advanced Cases Ward in P. K. Sanatorium, Mysore.

| Sl. No. | Items of work                                                                                                                                                                                                                  | Unit  | Rate      | Conts. | Cost  |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-----------|--------|-------|
|         |                                                                                                                                                                                                                                |       | Rs. a. p. |        | Rs.   |
| 1       | Earthwork excavation for foundation and filling in basement with consolidation .. ..                                                                                                                                           | Cyd.  | 0 3 9     | 191    | 45    |
| 2       | Burnt stone jelly concrete in lime mortar for foundation .. ..                                                                                                                                                                 | Cft.  | 0 3 6     | 1,789  | 391   |
| 3       | Burnt size stone in lime mortar for foundation and basement including bond stones 6' apart .. ..                                                                                                                               | "     | 0 5 0     | 4,458  | 1,393 |
| 4       | Burnt brick in mortar for superstructure .. ..                                                                                                                                                                                 | "     | 0 3 9     | 6,001  | 1,406 |
| 5       | Burnt brick in mortar for arch-work including centering, etc., complete .. ..                                                                                                                                                  | "     | 0 6 0     | 542    | 203   |
| 6       | Burnt stone slabs 6" thick roughly dressed and fixed in mortar .. ..                                                                                                                                                           | S.ft. | 0 6 0     | 2,054  | 770   |
| 7       | Two lines dressing to the burnt stone slabs on exposed faces .. ..                                                                                                                                                             | "     | 0 2 0     | 751    | 94    |
| 8       | Chunam plastering smooth including rounding corners, convex corners, being plastered with cement mortar for a width of 3" on both sides .. ..                                                                                  | Sqr.  | 3 0 0     | 98.84  | 297   |
| 9       | Wire cut bricks in composite mortar 1 in 6 pillars with cement concrete, base capital and bond slabs at every 3' circular in shape 14" diameter at bottom and 12" at top 12 feet in height including plastering complete .. .. | No.   | 15 0 0    | 20     | 300   |
| 10      | Dadoo painting to the walls around including sides of arch ways to a height of 1' with approved paint .. ..                                                                                                                    | Sqr.  | 3 8 0     | 13.12  | 46    |
| 11      | Dadooding with superior milk white and tints of light blue made with border and corner .. with Plaster of Paris painting, etc., complete .. ..                                                                                 | "     | 100 0 0   | 7.39   | 739   |
| 12      | Flooring with superior milk white and tints of light blue made on 3" concrete with composite mortar and with Plaster of Paris painting, etc., complete .. ..                                                                   | "     | 95 0 0    | 3.05   | 290   |
| 13      | Flooring with Venus tiles including laying in cement mortar on 3" granite jelly concrete and cement painting, etc., complete .. ..                                                                                             | "     | 56 0 0    | 36.22  | 2,028 |
| (a)     | Do Ravel company tile .. ..                                                                                                                                                                                                    | "     | ..        | ..     | ..    |
| 14      | Teakwood windows 4'×6' frames with 1½" thick glazed shutters of Morocco pinheaded glass ½" thick including brass parliamentary hinges, and brass tower bolts, spring catches, etc., with rectangular ventilator at top .. ..   | S.ft. | 1 10 0    | 165    | 268   |
| 15      | Teakwood windows with glazed shutters 1½" thick of Morocco pinheaded glass ½" thick, frames 3½"×4½" with brass parliamentary hinges and tower bolts and spring catches, etc. complete as per design .. ..                      | "     | 1 6 0     | 49     | 67    |

| Sl. No. | Items of work                                                                                                                                                                                                                                                                                                                                                                                                                            | Unit  | Rate      | Contents | Cost  |
|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-----------|----------|-------|
|         |                                                                                                                                                                                                                                                                                                                                                                                                                                          |       | Rs. a. p. |          | Rs.   |
| 16      | Teakwood ventilators $3\frac{1}{2} \times 4\frac{1}{2}$ " frames with $1\frac{1}{2}$ " thick shutters glazed with Morocco pinheaded glass $\frac{1}{8}$ " thick with brass hinges and movable arrangements as per design, etc., complete ..                                                                                                                                                                                              | S.ft. | 1 4 0     | 148      | 185   |
| 17      | Teakwood doors $4 \times 5$ " frames with $1\frac{1}{2}$ " thick $\frac{1}{2}$ " pannelled and $\frac{2}{3}$ " glazed shutters of Morocco pinheaded glass $\frac{1}{8}$ " thick and without bottom cills including copper oxidised or brass fittings, rim door locks with handles 3", finger plate $12 \times 4$ " as per design with 6" brass hinges and 2 (two) 6" hooks including semi-circular glazed ventilators on top complete .. | "     | 1 12 0    | 189      | 331   |
| 18      | Teakwood doors $4 \times 5$ " frames with $1\frac{1}{2}$ " thick pannelled shutters and without bottom cills including copper oxidised or brass fittings, rim door locks with handles 3" finger plate $12 \times 4$ " as per design with (six) 6" brass hinges and (two) 6" hooks, etc., complete ..                                                                                                                                     | "     | 1 8 0     | 64       | 96    |
| 18(a)   | Teakwood doors with $1\frac{1}{2}$ " thick pannelled shutters as per details under item 18 ..                                                                                                                                                                                                                                                                                                                                            | "     | 1 8 0     | 24       | 36    |
| 18(b)   | Providing and fixing B.R.C. weld mesh to windows the size of mesh being $3 \times 1$ " including painting with required paint two coats including teakwood patties ..                                                                                                                                                                                                                                                                    | "     | 0 9 0     | 139      | 104   |
| 19      | Teakwood doors $4 \times 3$ " frames $\frac{2}{3}$ " pannelled and $\frac{1}{2}$ " glazed with Morocco pinheaded glass $\frac{1}{8}$ " thick, shutters $1\frac{1}{2}$ " thick as per details under item 18 ..                                                                                                                                                                                                                            | "     | 1 8 0     | 182      | 273   |
| 20      | Rolled steel girders of B.S.S. tested including hoisting and fixing and with one coat of anti-corrosive paint including boxing complete ..                                                                                                                                                                                                                                                                                               | Cwt.  | 14 0 0    | 112      | 1568  |
| 21      | Cement concrete wall plate 1:2:4 jelly to be of granite metal $\frac{1}{2}$ " to $\frac{3}{4}$ " size on top course of wall to serve as wall plate ..                                                                                                                                                                                                                                                                                    | C.ft. | 0 10 0    | 227      | 142   |
| 22(a)   | Roofing with R.B.C. terrace as per standard specification for spans varying from 8' to 10' with negative bending moments and distribution bars 2" cross and longitudinal joints with 3" layer of surki concrete laid to proper slope to drain off rain water and 2 courses of flat tiles top and bottom plastering including coving with offsets as per required design ..                                                               | Sqr.  | 60 0 0    | 38.96    | 2,337 |
| 22(b)   | Do for spans above 10' up to 12' ..                                                                                                                                                                                                                                                                                                                                                                                                      | "     | 65 0 0    | 8.43     | 548   |
| 23      | R.C.C. chajja 4" thick with proper reinforcement and anchoring into walls including cement plastering and end cornice, etc., complete (projection up to 4' beyond wall) ..                                                                                                                                                                                                                                                               | S.ft. | 0 12 0    | 1,120    | 840   |
| 24      | R.C.C. chajja with heavy reinforcement and with 6' projection beyond wall with angle iron pieces, cross and longitudinal bars anchoring into walls including cement plastering and end cornice, etc., complete ..                                                                                                                                                                                                                        | S.ft. | 1 0 0     | 700      | 700   |
| 25      | Parapet wall $1\frac{1}{2}$ " high and 9" thick with base and top mouldings and with burnt brick in lime mortar with chunam plastering, etc., complete ..                                                                                                                                                                                                                                                                                | R.ft. | 0 14 0    | 2.6      | 189   |
| 26      | Constructing exmet wall with burnt brick in cement mortar and exmet at every 3rd course including chunam plastering complete ..                                                                                                                                                                                                                                                                                                          | S.ft. | 0 8 0     | 534      | 267   |
| 27      | Painting with laboratory green 2 coats ..                                                                                                                                                                                                                                                                                                                                                                                                | Sqr.  | 4 8 0     | 5.43     | 24    |
| 28      | Wax polishing to doors of interior walls ..                                                                                                                                                                                                                                                                                                                                                                                              | "     | 7 0 0     | 8.71     | 61    |
| 29      | White and colour washing 2 coats ..                                                                                                                                                                                                                                                                                                                                                                                                      | "     | 0 5 0     | 98.84    | 31    |
| 30      | Providing and fixing R.C.C. fret work as per approved design ..                                                                                                                                                                                                                                                                                                                                                                          | S.ft. | 1 0 0     | 92       | 92    |
| 31      | Providing and fixing cement asbestos rain water down pipes with bends, heads, etc., complete ..                                                                                                                                                                                                                                                                                                                                          | R.ft. | 1 0 0     | 100      | 100   |

Notification dated 18th August 1939.

It is hereby notified that the shop at the North-west corner of Curzon Park, near the Wesleyan Mission School Building, opposite to the Lansdowne Bazaar buildings will be rented out for opening shops.

Intending tenants may submit their tender to the Assistant Engineer, Headquarter Range, Mysore, on or before the 4th September 1939.

2. The tenders should be submitted in sealed covers, accompanied by an earnest money of Rs. 50 and superscribed "Tender for taking over on lease the shop at the north-west corner of Garden Park, Mysore," the name and address of the tenant being noted in full on the cover and addressed to the Assistant Engineer, Headquarter Range, Mysore.

3. The accommodation available in the shop is noted below. The tenders of Hotel and Restaurant keepers, oil mongers and provision dealers, etc., will not be considered.

4. The successful tenderer should, within eight days after the acceptance of the tender, execute an agreement in the usual form, after paying a security deposit equal to the number of months the usual rent due for each month in advance on or before the 5th of each month. Failure to do so on this condition will entail forfeiture of the security deposit and the immediate cancellation of the tender.

5. The Assistant Engineer reserves to himself the right to accept or refuse any tender without assigning any reason whatever.

The lease will, in the first instance, be for eleven months only, which can be renewed or renewed after the expiry of the above period at the discretion of the Assistant Engineer.

- (1) One oblong hall measuring 61' in length and 17' wide, with a verandah and a door on the north end with a verandah of 18' x 4' on the north side.
- (2) Six shops, each with one door in the north measuring 12' x 7' and 7 doors on the west side (Garden Park and Landable Buildings) measuring 4½' x 6½'.

M. N. LAKSHMINARAYAN,  
Assistant Engineer.

#### MANDYA DIVISION.

*Abstract Notification dated 3rd August 1939.*

The attention of the public is invited to the notification on pages 1547-1549, Part VI of the *Mysore Gazette*, dated 10th August 1939, inviting tenders for the work of increasing the capacity of Herge Amballi tank in Narasimha Taluk.

The last date fixed for the receipt of tenders in this office is 12 NOON on 20th August 1939.

*Abstract Notification dated 3rd August 1939.*

The attention of the public is invited to the notification on pages 1549-1551, Part VI of the *Mysore Gazette*, dated 10th August 1939, inviting tenders for the work of restoring the tank in Mangamangala Taluk.

The last date fixed for the receipt of tenders in this office is 12 NOON on 26th August 1939.

*Abstract Notification dated 13th August 1939.*

The attention of the public is hereby invited to the notification on pages 1598-1600, Part VI of the issue of the *Mysore Gazette*, dated 13th August 1939, inviting tenders for the work of constructing the Administrative Block at the Government Bazaar at Krishnarajpet. A Form of tender will be supplied on each tender in the form of a copy to the contractors.

The last date fixed for the receipt of tenders in this office is 12 noon on 14th August 1939.

M. V. KRISHNASWAMY IYENGAR,  
Executive Engineer.

#### MASANA DIVISION.

*Abstract Notification dated 4th August 1939.*

The attention of the public is drawn to the tender notification, published in pages 1552-1559, Part VI of the *Mysore Gazette*, dated 10th August 1939, calling for tenders for constructing one block of Cooly Quarters of five rooms and one block of Cooly Quarters of two rooms at Sravanabelagola, Channarayana Taluk, for the use of Electrical Department.

The last date for the receipt of tenders is 25th August 1939.

*Abstract Notification dated 4th August 1939.*

The attention of the public is drawn to the tender notification published in pages 1554-1559 of Part VI of the *Mysore Gazette*, dated the 10th August 1939, calling for tenders for constructing Electrical Buildings at Channarayapatna, such as:—

- (1) Constructing Office and Stores Building.
- (2) One double block of Operator's Quarters.
- (3) One block of Cooly Quarters of five rooms.
- (4) One block of Cooly Quarters of four rooms.
- (5) One block of Line Inspector's Quarters.
- (6) One block of Cooly Quarters of two rooms.

The last date for the receipt of tenders is 25th August 1939.

P. SUBBA RAO,  
*Executive Engineer.*

## ANJANAPUR DIVISION.

*Abstract Notification dated 10th August 1939.*

The attention of the public is invited to the notification, published on page 1601, Part VI of the *Mysore Gazette*, dated 17th August 1939, regarding the public auction of the Tools and Plant articles on 19th September 1939, 10 A.M.

M. VENKATAKRISHNA RAO,  
*Executive Engineer.*

## KADUR DIVISION.

*Notification dated 17th August 1939.*

1. Sealed tenders will be received at the Office of the Executive Engineer, Kadur Division, Chikmagalur, up to 3 P.M. on 8th September 1939, for the work of repairing the big car of Sree Kalaswaraswamy temple at Kalasa, Mudgere Taluk.
2. Tenders in the prescribed form obtainable at four annas per copy from the Office of the Executive Engineer, Kadur Division, should be addressed to the Executive Engineer, Kadur Division, Chikmagalur, in a sealed cover and superscribed as "Tender for the work of Repairing the big car of Sree Kalaswaraswami temple at Kalasa, Mudgere Taluk." The name of the tenderer should also be superscribed on the top of the cover.
3. Each tender must be accompanied by a Treasury challan for Rs. 175 (Rupees one hundred and seventy-five only) for having credited this earnest money to the head "(a) P. W. Deposits" in any approved Government Treasury. The earnest money of the successful tenderer will be retained as security deposit for due fulfilment of the contract. Such a deposit will not carry any interest.
4. The tenders will be opened in the presence of such tenderers who wish to be present on 8th September 1939 at Chikmagalur. The final acceptance of the tender will rest with the Executive Engineer, who does not bind himself to accept the lowest or any tender, or to assign any reason whatever for the rejection of any.
5. The name of the successful tenderer will be posted on the Notice Board in the Executive Engineer's Office in due course. Within eight days of the acceptance of the tender, the successful tenderer will be required to execute an agreement in the departmental schedule contract form, for the due fulfilment of the contract.
6. Failure to comply with the condition 5 above, or to agree to carry out the work in accordance with the specifications and agreements in force will entail forfeiture of the earnest money.
7. The earnest money of rejected tenders will be returned on submission of the receipt originally granted, along with an application to the Executive Engineer.
8. Copies of contract documents, schedules and drawings may be seen at any time at the Executive Engineer's Office, Chikmagalur, on all working days between 11 A.M. and 5 P.M.
9. Specific rates should be given for each item in the schedule accompanying the tender and the rates should be in rupees, annas and pies and expressed in words and figures.
10. Any rates or lumpsum amounts for the items not called for, if tendered by the tenderer, will not be taken notice of. The rates for such items may be entered in a separate schedule with date and reasons for the same.
11. No alterations which are made by the tenderers in the tender form in the nomenclature of the items of work will be recognised and if corrections are made the tenders are liable to rejection.
12. There should be no alterations or erasures in the tenders in the rates of items and any corrections made in the rates should be attested to, and the number of corrections, if any, in each page noted at the foot of the same by the tenderer.
13. No reference should be made to the Public Works Department schedule of rates.
14. In the event of the tender being submitted by a firm, it must be signed separately and severally by each member thereof, or in the event of absence of any partner, it must be signed on his behalf by a person holding power-of-attorney authorising him to do so.



| No.  | Items of work                                                                                                                                                        | Unit  | Rate      | Quantity | Cost |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-----------|----------|------|
|      |                                                                                                                                                                      |       | Rs. a. p. |          | Rs.  |
| 6    | Removing and refixing old scantlings of the above portion after necessary repairs                                                                                    | C.ft. | ..        | 75       |      |
| 7    | Removing and refixing with necessary repairs the top base of peeta 8' diameter                                                                                       | S.ft. | ..        | 69       |      |
| 8(a) | Removing and refixing the images in good conditions after necessary cleaning and repair, etc., big size images of 'C' position                                       | "     | ..        | 19       |      |
| (b)  | Do carving with small carved images of position 'B', <i>vide drawing</i> . This consisting of flowers, ornamental figures, etc.                                      | "     | ..        | 43       |      |
| (c)  | Do ornamental small images with carvings on planks of wood, etc., of the portion 'A', <i>vide drawing</i> with necessary repairs, etc., complete                     | "     | ..        | 30       |      |
| 9(a) | Providing new big size images with carvings, ornamentation, etc., for the portion 'C', <i>vide drawing</i> in place of damaged ones                                  | "     | ..        | 19       |      |
| (b)  | Providing and fixing new big size images for the portion 'B', <i>vide drawing</i> ornamental figures, flowers, etc., of big size                                     | "     | ..        | 43       |      |
| (c)  | Do for the portion 'A' small images with carvings and ornamentation on planks                                                                                        | "     | ..        | 30       |      |
| 10   | Providing a new teakwood seat for the idol with carvings of approved design                                                                                          | L. S. |           |          |      |
| 11   | Iron fittings such as bolts, nuts, screws, iron strops, anchoring bolts, long bar, hooks, rings, etc. required for fixing wooden framings including fixing charges   | "     | ..        |          |      |
| 12   | Providing new ornamental wooden hands with carvings of small images, etc., for the exterior portions of 'D' 'E', <i>vide drawing</i>                                 | S.ft. |           | 33       |      |
| 13   | Painting the images, carvings and ornamentations with two coats of Bhadravati wood preservative for A. B. C. D. E. portions, <i>vide drawing</i> including wood work | L. S. |           |          |      |
| 14   | Providing iron chains for dragging the car                                                                                                                           | R.ft. | ..        | 100      |      |
| 15   | Miscellaneous parts, new, required for the car which are found necessary during execution                                                                            | L. S. | ..        |          |      |

M. A. RAMANUJAM,  
Executive Engineer.

### MEDICAL DEPARTMENT

#### MINTO OPHTHALMIC HOSPITAL, BANGALORE.

*Tender Notice*, dated 17th August 1939.

Notice is hereby given that sealed tenders in triplicate on half-sheet foolscap size paper will be received at the Office of the Secretary (in Victoria Hospital), Victoria, Mint and Vani Vilas Hospitals, Bangalore, on Monday the 25th September 1939 at 11 A.M., for the supply of bedding and clothing required for the use of the Minto Ophthalmic Hospital, Bangalore, for the year 1939-40.

2. No tenders will be received after the date and hour above-mentioned.

3. Tenders to be superscribed "Tender for the supply of bedding and clothing" to the Minto Ophthalmic Hospital, Bangalore.

4. No tender will be received unless accompanied by a deposit of rupees fifty (50) in cash or currency notes or Treasury Receipts.

5. Tenders will be opened by the Secretary at his office (Victoria Hospital) on the date and at the hour above-mentioned, in the presence of such tenderers as may choose to attend.

6. The rate for each item must be specified in figures as well as in words in ink and they must be for the particular kind or brand of the article as specified in the list appended hereto. The value of each tender must be worked out according to the rates tendered and the total value must also be entered in words and in ink. Tenders not conforming to this rule will be rejected.

7. The full quantities and all the items stated in the list are not guaranteed.

8. The Senior Surgeon does not bind himself to accept the lowest or any other tender or to assign any reason for not accepting any tender. He may accept one or more items in any one tender without accepting the other items.